



On the cover: Mk VII Rollo-Mixer model 98-200/75s batch mixer is shown discharging a plastic pellet mixture for extrusion of ethylene propylene diene monomer (EPDM) rubber roofing membrane at a Pennsylvania plant that blends construction materials. Mixer has a 200-cubic-foot load rating at 75 pounds per cubic foot. Mixer is front-loaded through a material transfer receiver, blends 15,000-pound batches in 3 minutes, and discharges the material into totes. Mixer includes a load-cell scale system and an air-purge amplifier for quick cleanout. Courtesy of Continental Products, Osseo, WI, 414-964-0640 (www.continentalrollomixer.com).

EDITOR'S NOTE

10 An information-filled 2018

Jan Brenny

MIXING AND BLENDING



44 Case history: Mixer thoroughly blends wood powders

48 Product summary

96 Suppliers' tips

Suppliers discuss the importance of adhering to recommended "total" and "working" mixing volumes.

GENERAL FEATURES



30 Drying Desk

Columnist John J. Walsh explains practical methods for increasing your dryer's production capacity.

53 Using vacuum pneumatic conveying to improve pharmaceutical processing

Doan Pendleton

61 Selecting sanitary processing equipment

Scott Lodermeier

67 Optimizing your dust collection system for process variables

Travis Haynam

75 EnviroPlant

76 Agglomeration Advisor

Columnist Eric Matovich uses a case study to illustrate points to consider when integrating agglomeration into a manufacturing process.

83 Trade show preview: ICACC18

DEPARTMENTS

14 Industry news

26 Markets update

28 Research notes

36 Special section:

Bulk bags and equipment

84 Calendar

87 Continuing education

91 What's new

92 Supplier notes

92 People news

92 Product news

94 Classified advertising

95 Advertiser index